


976nm~980nm 10mW Single Mode Butterfly (BTF) Package Pigtailed Laser Diode with PD | Built-in TEC cooler
980nm 10mW SM Fiber Coupled LD with 14-Pin package | Infrared Laser Diode Module | Built-in Photodiode
WSLX-980-010m-4-T-PD **Wavespectrum Laser Group** **www.wavespectrum-laser.com**

980nm Pigtailed Diode Laser	10mW/SM Fiber	en.wavespectrum-laser.com.cn
------------------------------------	----------------------	-------------------------------------

PARAMETER	SYMBOL	VALUE	UNIT
Reverse Voltage	V_r	2.0	V
Operating Temperature	T_{op}	-10~+40	°C
Storage Temperature	T_{stg}	-15~+80	°C
Lead soldering temperature (5 sec.)	T_{is}	250	°C

Features:

- 980nm
- With SM Fiber
- 14-Pin Package
- Built-in TEC Cooler



Applications:


- Medical laser treatment
- Sensor
- Others

Specifications	WSLX-980-010m-4-T-PD		
-----------------------	-----------------------------	--	--

	Min	Type	Max
Center Wavelength@25°C	970nm	980nm	990nm
Recommend Operating Temperature	25°C		
Output Power	----	10mW	----
Fiber Type	Single Mode Fiber		
Fiber Core	6um		
Threshold Current (Typ.)	----	15mA	30mA
Operating Current (Typ.)	----	80mA	100mA
Operating Voltage	----	1.6V	2.2V
TEC Max Current	1.8A		
TEC Max Voltage	2.5V		
Thermistor	10K		
Fiber Connector	FC/SMA905		
Fiber Length	80cm		
Package Style	14-Pin		



14-Pin Package View



Pin Out:

PIN	FUNCTION	PIN	FUNCTION
1	TEC(+)	14	TEC(-)
2	THERMISTOR	13	CASE
3	PD(+)	12	NC
4	PD(-)	11	LD(-)
5	THERMISTOR	10	LD(+)
6	NC	9	NC
7	NC	8	NC

Electrically shorten LD module and store in non-extreme conditions.
Suggest using the constant current power supply.

