


**520nm 30mW Coaxial Diode Laser with Polarization Maintaining Fiber| Green Laser Module**  
**515nm~520nm~530nm PM Fiber Coupled Green LD with SMF | Built-in PD Optional**  
 WSLP-520-030m-PM      Wavespectrum Laser Group      www.wavespectrum-laser.com

<b>520nm Pigtailed Diode Laser</b>	<b>30mW/PMF</b>	<b>en.wavespectrum-laser.com.cn</b>
------------------------------------	-----------------	-------------------------------------

PARAMETER	SYMBOL	VALUE	UNIT
Reverse Voltage	$V_r$	2.0	V
Operating Temperature	$T_{op}$	-20 ~ +60	°C
Storage Temperature	$T_{stg}$	-40 ~ +85	°C
Lead soldering temperature (10 sec.)	$T_{is}$	260	°C



<p><b>Features:</b></p> <ul style="list-style-type: none"> <li>● 520nm Green Diode Laser</li> <li>● PM Fiber</li> <li>● High Reliability</li> <li>● High Polarization Extinction Ratio</li> </ul> <p><b>Applications:</b></p> <ul style="list-style-type: none"> <li>● Biological Instruments</li> <li>● Analytical Equipment</li> <li>● Others</li> </ul>	
--	--

Specifications	WSLP-520-030m-PM		
	Min	Type	Max
Center Wavelength@25°C	510nm	520nm	530nm
Spectral Width (FWHM)	----	2.0nm	----
Output Power	----	30mW	----
Fiber Type	Polarization Maintaining Fiber		
Fiber Core	3um		
Polarization Extinction Ratio	13dB	15dB	----
Recommend Operating Temperature	25°C		
Fiber Connector	FC/APC		
Fiber Length	----	80cm	100cm
Threshold Current	----	65mA	95mA
Operating Current	----	270mA	290mA
Operating Voltage	----	7.0V	8.0V
Photodiode	Optional		
Package Style	Coaxial or B82		

High Polarization Extinction Ratio (PER) Version Laser Module is also available, please contact us.



**Coaxial Package View: (Part Number: WSLP-520-030m-PM)**

**B82 Package View: (Part Number: WSLP-520-030m-PM-B)**

**PIN Bottom View:**


<b>1</b>	<b>LD(+)</b>
<b>2</b>	<b>GND</b>
<b>3</b>	<b>LD(-)</b>



Electrically shorten LD module and store in non-extreme conditions.  
Suggest using the constant current power supply.

