



910nm~915nm 30W Fiber Coupled Laser Diode Module | Medical Cure

915nm 30W High Power Pigtailed Diode Laser | T14 Package| 105um 200um Fiber optional | High Power LD
 WSLX-915-030-M-T14 Wavespectrum Laser Group www.wavespectrum-laser.com

PARAMETER	SYMBOL	VALUE		UNIT
Reverse Voltage	V _r	2.0		V
Operating Temperature	T _{op}	+10 ~ +35		°C
Storage Temperature	T _{stg}	-20 ~ +80		°C
Lead soldering temperature (10 sec.)	T _{is}	260		°C
Features: 915nm 30W Output Power 105um Fiber Core - Long Lifetime - High Stability				
Applications: - Printing - Medical Laser Treatment - Others				
Specifications		WSLX-915-030-M-T14		
		Min	Type	Max
Center Wavelength@25°C		915nm±10nm		
Output Power		25W	30W	----
Spectral Width (FWHM)		----	5nm	----
Recommended Case Temperature		25°C		
Temperature Coefficient of Wavelength		0.3nm / °C		
Threshold Current (Typ.)		----	0.5A	1.0A
Operating Current (Typ.)		----	12.0A	13.0A
Operating Voltage		----	5.7V	6.6V
Fiber Core Diameter		105um		
Fiber Numerical Aperture		0.22 N.A.		
Fiber Length		>80cm		
Connector Type		SMA905/ST/FC/SC		
Package Style		T14		



T14 Package View:



Electrically shorten LD module and store in non-extreme conditions.
Suggest using the constant current power supply.

